

celesta®

Monocrystalline Solar Module

CL260M-60

60 CELL

Mono Crystalline Module

16.01%

Maximum Efficiency

260W

Power Output Range

0/+3W

Positive Power Tolerance

Function Features



5 Busbar Solar Cell

5 busbar solar cell adopts new technology to improve the efficiency of modules, offers a better aesthetic appearance, making it perfect for rooftop installation.



High Efficiency

High module conversion efficiency (up to 16.01%), through innovative manufacturing technology.



Severe Weather Resilience

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).



Low-light Performance

Advanced glass and solar cell surface texturing allow for excellent performance in low-light environments.



Maximized Energy Harvest

Impedance matching technology eliminates mismatch losses, more power from each module bin.




Higher quality assurance

100% EL test before and after lamination, and finished products EL test, providing higher quality assurance.


LINEAR PERFORMANCE WARRANTY

10-Year Product Warranty

25-Year Linear Power Warranty



Engineering Drawings




Packaging Configuration

(Two boxes=One pallet)

26pcs/box, 52pcs/pallet, 728pcs/40'GP Container

Current-Voltage Curves



Mechanical Characteristics

Cell Type	Monocrystalline 156×156mm
Cell Number	60 (6×10)
Dimensions	1640×990×40mm
Weight	17.00 kg
Front Glass	3.2mm, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67 Rated
Output Cables	1x4.0mm², Length:900mm

Technical Specifications

Module Type	CL260M-60
Maximum Power (Pmax)	260Wp
Maximum Power Voltage (Vmp)	30.7V
Maximum Power Current (Imp)	8.47A
Open-circuit Voltage (Voc)	38.9V
Short-circuit Current (Isc)	9.18A
Module Efficiency STC (%)	16.01%
Operating Temperature(°C)	-40°C ~ +85°C
Maximum system voltage	1000VDC (IEC)
Maximum series fuse rating	15A
Power tolerance	0~+3%
Temperature coefficients of Pmax	-0.39%/°C
Temperature coefficients of Voc	-0.29%/°C
Temperature coefficients of Isc	0.05%/°C
Nominal operating cell temperature (NOCT)	45±2°C

STC:



Irradiance 1000W/m²



Cell Temperature 25°C



AM=1.5



Wind Speed 1m/s



Ambient Temperature 20°C



AM=1.5

* Power measurement tolerance: ± 3%